Jaw Coupling



The Finer Jaw Coupling is recognised across a large range of industries. The Jaw Coupling is highly resilient, it does not require any lubrication and can work in environments contaminated with oil, dirt, sand, moisture and grease.


The rubber insert is designed to absorb shock loading and does not allow for any metal on metal contact. Finer Power Transmissions stocks both the Spider Elements as well as the Wrap Element Kits and Spacers.

Finer Power Transmissions stocks a range of jaw couplings in a variety of pre-bored and keyed sizes.



Size	Pilot	Element*	Flamont*	Flomont*	Flamont*	Flomont*	Flomont*	Flomont*	Mron	1/:4											- N	/letric	(mm)										
	Bore		Wrap	Kit	9	10	11	12	14	16	18	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50	55	60						
L050	✓	✓			✓	✓	✓	✓	✓																									
L070	✓	✓				✓	✓	✓	✓	✓	✓	✓																						
L075	✓	✓						✓	✓	✓	✓	✓	✓	✓																				
L095	✓	✓	✓	✓					✓	✓	✓	✓	✓	✓	✓	✓	✓																	
L100	✓	✓	✓	✓							✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓													
L110	✓	✓	✓	✓									✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓											
L150	✓	✓	✓	✓											✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓									
L190	✓	✓	✓														✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓						
L225 PB	✓	✓	✓																															

*Available in Standard & Polyurethane



Size					Spacers										
	3/8	1/2	5/8	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2	1 5/8	2	100mm	140mm	180mm
L050	✓	✓	✓												
L070	✓	✓	✓	✓											
L075	√	✓	✓	✓	✓										
L095		✓	✓	✓	✓	✓	✓								
L100			✓	✓	✓	✓	✓	✓					✓	✓	
L110					✓	✓	✓	✓	✓	✓			✓	✓	
L150						✓	✓	✓	✓	✓			✓	✓	✓
L190									✓	✓	✓	✓	✓	✓	✓
L225 PB															

Coupling	Type	А	В	С	D	Stock Bore	Weigh	Max Bore.	
Coupling	туре	A	D	U U	U	Stock bole	Min. Bore	Max. Bore	IVIAX DUTE.
L070PB	1	35	53	13	19	6	0.26	0.24	19
L075PB	1	44.5	53	13	21	6	0.45	0.39	22
L095PB	1	54	65	13	25	11	0.79	0.69	29
L100PB	1	65	86	19	35	11	1.55	1.32	35
L110PB	1	84	110	24	43	16	2.93	2.55	42
L150PB	1	96	113	25	45	16	4.06	3.51	48
L190PB	1	115	133						
L225PB	1	127	155						

Coupling	May DDM	Torque in I he	Horsepower capacities at indicated speeds (RPM)											
Coupling	Max. RPM	Torque in Lbs.	50	100	300	600	900	1200	1800	3600				
L050 PB														
L070 PB	14000	44.1	-	0.07	0.21	0.42	0.63	0.84	1.26	2.52				
L075 PB	11000	88.2	0.035	0.14	0.38	0.76	1.26	1.68	2.52	1.04				
L095 PB	9000	189.0	0.115	0.30	0.90	1.80	2.70	3.60	5.40	10.80				
L100 PB	7000	416.0	0.330	0.66	1.98	3.96	5.94	7.92	11.90	23.80				
L110 PB	5000	788.0	.630	1.25	3.75	7.50	11.30	15.00	22.50	45.00				
L150 PB	5000	1260.0	1.000	2.00	6.00	12.00	18.00	24.00	36.00	72.00				