



200

SY Chain No. (ANSI)	Dimensions - mm											Average Ultimate Strength Kn	Maximum Allowable Load kN	Average Chain Weight kg/m	
	Pitch P	Bushing		Pin				Plate		Trans. Pitch TP					
		Width W	Dia. R	Dia. D	Length		Height H	Thick. T							
					LR	LC	L1	L2							
200	63.5	38.1	39.67	19.83	78.5	87.0	39.3	47.7	59.8	8.0	71.6	-	451	93	16.93
200-2					150.2	158.7	75.1	83.6				902	122	33.73	
200-3					221.7	230.2	110.9	119.3				1353	179	50.53	
200-4					293.3	302.4	146.7	155.7				1804	236	67.34	
200-5					365.5	374	182.8	191.2				2255	279	84.14	
200-6					437.1	445.6	218.6	227				2706	329	100.94	

240

SY Chain No. (ANSI)	Dimensions - mm											Average Ultimate Strength Kn	Maximum Allowable Load kN	Average Chain Weight kg/m	
	Pitch P	Bushing		Pin				Plate		Trans. Pitch TP					
		Width W	Dia. R	Dia. D	Length		Height H	Thick. T							
					LR	LC	L1	L2							
240	76.2	47.63	47.63	23.78	96.4	104.1	48.2	55.9	70.3	9.5	87.8	-	677	129	23.64
240-2					184.2	191.8	92.1	99.7				1354	167	47.13	
240-3					272	279.6	136.0	143.6				2031	245	70.61	
240-4					359.8	367.4	179.9	187.5				2708	324	94.09	
240-5					447.6	455.2	223.8	231.4				3385	383	117.56	
240-6					535.5	543	267.8	275.2				4062	451	141.06	