

Timing belts made of Polyurethane with steel lacing tension cord and trapezoid formed teeth.

Applications:

Type T2,5: power transmission up to 0.5 kW, electro mechanical design, e.g. film cameras Type T5: power transmission up to 2 kW, e.g. grinding, kitchen and office machines Type T10: power transmission up to 20 kW, e.g. textile, printing and tool machines, pumps, compressors, bellows

Finer Power Transmissions stocks a range of Strongbelt sleeves, these are cut to ordered widths.

RANGE	Min. Length (mm)	Max. Length (mm)
T2.5	120	950
T5	165	1440
T10	260	2250
AT5	225	1500
AT10	500	1940

For detailed listing of Polyurethane Range please visit: - finerpt.com/timingbelts

- page 153 of New Finer Power Transmissions Catalogue



10% OFF ALL PTS Polyurethane Timing Belt Orders Over \$100*

(Conditions: *This Special <u>MUST</u> be mentioned on order or at time of ordering for discount to apply. This offer cannot be combined with any other special or freight deals. Finer Power Transmissions will honour the special/deal that gives you the biggest saving. Special is valid until Friday 30th Aug)



Head Office (VIC)

(P) 03 9791 2444 (F) 03 9791 3344

New South Wales (P) 02 9671 6600

(F) 02 9676 8200

Queensland

(P) 07 3865 5002

(F) 07 3865 5202









