



Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)	Factor	Limiting speeds(min-1)		Bearing No.	Mounting dimensions(mm)			Mass(kg)
d	D	B	r min.	Cr	Cor	Cu	fo	Grease lub.	Oil lub.		da(min)	Da(max)	ra(max)	
15	32	8	0.3	7	2.85	0.15	13.9	23 000	28 000	16002	17	30	0.3	0.025
17	35	8	0.3	7.5	3.25	0.17	14.4	21 000	25 000	16003	19	33	0.3	0.032
20	42	8	0.3	9.9	4.5	0.29	14.4	17 000	21 000	16004	22	40	0.3	0.05
25	47	8	0.3	11.1	5.6	0.34	15.1	15 000	18 000	16005	27	45	0.3	0.06
30	55	9	0.3	14.1	7.35	0.44	15.2	13 000	15 000	16006	32	53	0.3	0.085
35	62	9	0.3	15.3	8.85	0.5	15.7	11 000	13 000	16007	37	60	0.3	0.11
40	68	9	0.3	15.8	9.65	0.53	16	9 800	12 000	16008	42	66	0.3	0.125
45	75	10	0.6	19.4	12.3	0.67	16	8 900	10 000	16009	49	71	0.6	0.17
50	80	10	0.6	20	13.3	0.71	16.2	8 200	9 700	16010	54	76	0.6	0.18
55	90	11	0.6	24.2	16.3	0.88	16.2	7 400	8 800	16011	59	86	0.6	0.26
60	95	11	0.6	24.8	17.6	0.93	16.4	6 900	8 100	16012	64	91	0.6	0.28
65	100	11	0.6	21.4	16	0.83	16.5	6 600	7 800	16013	69	96	0.6	0.3
70	110	13	0.6	37.6	25.6	1.4	16	6 100	7 200	16014	74	106	0.6	0.433
75	115	13	0.6	34.4	25.3	1.35	16.4	5 700	6 700	16015	79	111	0.6	0.457
80	125	14	0.6	39.7	29.7	1.5	16.4	5 200	6 100	16016	84	121	0.6	0.597
85	130	14	0.6	40.8	31.7	1.55	16.5	4 900	5 800	16017	89	126	0.6	0.626
90	140	16	1	49.9	37	1.85	16.3	4 700	5 600	16018	95	135	1	0.848
95	145	16	1	51.5	39.6	1.9	16.4	4 500	5 300	16019	100	140	1	0.885
100	150	16	1	53	42.1	1.95	16.5	4 300	5 100	16020	105	145	1	0.91
105	160	18	1	52.3	42.2	1.9	16.5	4 100	4 800	16021	110	155	1	1.2
110	170	19	1	71.8	56.7	2.55	16.3	3 800	4 500	16022	115	165	1	1.46
120	180	19	1	79	63.3	2.75	16.4	3 600	4 200	16024	125	175	1	1.8
130	200	22	1.1	89.1	74.8	3.05	11.2	3 000	3 600	16026	136.5	193.5	1	2.69
140	210	22	1.1	82.2	71.1	2.80	16.5	2 900	3 400	16028	146.5	203.5	1	2.86