



Boundary dimension (mm)				Basic load ratings (N)		speed rating	Bearing num- bers	Abutment and fillet dimensions(mm)				Mass (kg)
d	D	B	rs min	dynamic	static	grease (rpm)		Ds	Ds	dh	R	
				Cr	Cor			min	max	max	max	
10	30	14	0.6	5070	2360	17000	62200 2RS	14	14.5	26	0.6	0.04
12	32	14	0.6	6890	3100	15000	62201 2RS	16	16	28	0.6	0.045
	37	17	1	9750	4150	14000	62301 2RS	17	17	32	1	0.07
15	35	14	0.6	7800	3750	13000	62202 2RS	19	19	31	0.6	0.054
	42	17	1	11400	5400	12000	62302 2RS	20	20	37	1	0.11
17	40	16	0.6	9560	4750	12000	62203 2RS	21	21	36	0.6	0.083
	47	19	1	13500	6550	11000	62303 2RS	22	23	43	1	0.15
20	47	18	0.6	12700	6550	10000	62204 2RS	25	25	42	1	0.13
	52	21	1.1	15900	7800	9500	62304 2RS	26	27	45	1	0.2
25	52	18	0.1	14000	7800	8500	62205 2RS	30	31	47	1	0.15
	62	24	1.1	22500	11600	7500	62305 2RS	31	33	55.5	1	0.32
30	62	20	1	19500	11200	7500	62206 2RS	35	37	57	1	0.24
	72	27	1.1	28100	16000	6300	62306 2RS	36.5	41.5	65.5	1	0.48
35	72	23	1.1	25500	15300	6300	62207 2RS	41.5	43.5	65.5	1	0.37
	80	31	1.5	33200	19000	6000	62307 2RS	43	44	72	1.5	0.66
40	80	23	1.1	30700	19000	5600	62208 2RS	46.5	49.5	73.5	1	0.44
45	85	23	1.1	33200	21600	5000	62209 2RS	51.5	54	78.5	1	0.48
50	90	23	1.1	35100	23200	4800	62210 2RS	56.5	58	83.5	1	0.52
10	26	12	0.3	4620	1960	19000	63000 2RS	12	12.5	24	0.3	0.025
12	28	12	0.3	5070	2360	17000	63001 2RS	14	14.5	26	0.3	0.029
15	32	13	0.3	5590	2850	14000	63002 2RS	17	18.0	30	0.3	0.039
17	35	14	0.3	6050	3250	13000	63003 2RS	19	20.0	33	0.3	0.052
20	42	16	0.6	9360	5000	11000	63004 2RS	24	24.5	38	0.6	0.086
25	47	16	0.6	11200	6550	9500	63005 2RS	29	29.0	43	0.6	0.100
30	55	19	1.0	13300	8300	8000	63006 2RS	35	35.5	50	1	0.160
35	62	20	1.0	15900	10200	7000	63007 2RS	40	40.5	57	1	0.210