## Open Ended Timing Belts



| Section | Pitch | Tooth Height | Thickness | Cross Section  | Roll Length |
|---------|-------|--------------|-----------|--|-------------|
| 5M      | 5.00  | 2.10         | 3.8       | Pech   | 50          |
| 8M      | 8.00  | 3.48         | 6.0       | PRCh W   | 50          |
| T5      | 5.00  | 1.2          | 2.2       | 5.00<br>100-40-40-40-40-40-40-40-40-40-40-40-40-4  | 50          |
| T10     | 10.00 | 2.5          | 4.5       | 10.00 Fro.6 Fro.6 St. 31 St. 3 | 50          |
| AT5     | 5.00  | 1.2          | 2.7       | 5.00<br>Fro.86 50 250  | 50          |
| AT10    | 10.00 | 2.5          | 5         | 10.00<br>fa0.40<br>Fr1.25<br>5.00  | 50          |
| XL      | 5.080 | 1.27         | 2.3       | 2.3 i<br>1.27<br>0.38<br>0.38  | 50          |
| L       | 9.525 | 1.91         | 3.6       | 3.6.   | 50          |
| Н       | 12.70 | 2.29         | 4.3       | 4.3 f<br>2.29<br>1.02<br>1.02<br>1.02  | 50          |