

# Find the right product for your application



## General Purpose

- LOCTITE® LB 8150™
- LOCTITE® LB 8060™
- LOCTITE® LB 8151™
- LOCTITE® LB 8008™
- LOCTITE® LB 771™

## High Performance

- LOCTITE® LB 8009™
- LOCTITE® LB 8070™

## Speciality

- LOCTITE® LB 8014™
- LOCTITE® LB 8044™
- LOCTITE® LB 8700™
- LOCTITE® LB 8504™

## General Purpose



**LB 8150™**  
Silver



**Temperature Range:**  
-29°C to 871°C



**Metal Free:** No

**Colour:** Silver  
**Solid Lubricating Agent:** Aluminium / Graphite



**LB 8060™**  
Silver (Stick)



**Temperature Range:**  
-29°C to 871°C



**Metal Free:** No

**Colour:** Silver  
**Solid Lubricating Agent:** Aluminium / Graphite / Wax



**LB 8151™**  
Silver (Aerosol)



**Temperature Range:**  
-29°C to 871°C



**Metal Free:** No

**Colour:** Silver  
**Solid Lubricating Agent:** Aluminium / Graphite



**LB 8008™**  
Copper C5-A



**Temperature Range:**  
-29°C to 982°C



**Metal Free:** No

**Colour:** Copper  
**Solid Lubricating Agent:** Copper / Graphite

## High Performance



**LB 8009™**  
Heavy Duty



**Temperature Range:**  
-29°C to 1315°C



**Metal Free:** Yes

**Colour:** Black  
**Solid Lubricating Agent:** Calcium Fluoride / Graphite



**LB 8070™**  
Heavy Duty (Stick)



**Temperature Range:**  
-29°C to 1315°C



**Metal Free:** Yes

**Colour:** Black  
**Solid Lubricating Agent:** Calcium Fluoride / Graphite / Wax



**LB 771™**  
Nickel



**Temperature Range:**  
-29°C to 1315°C



**Metal Free:** No

**Colour:** Silver  
**Solid Lubricating Agent:** Nickel / Graphite

