

Find the right product for your application



General Purpose

- LOCTITE® LB 8150™
- LOCTITE® LB 8060™
- LOCTITE® LB 8151™
- LOCTITE® LB 8008™
- LOCTITE® LB 771™

High Performance

- LOCTITE® LB 8009™
- LOCTITE® LB 8070™

Speciality

- LOCTITE® LB 8014™
- LOCTITE® LB 8044™
- LOCTITE® LB 8700™
- LOCTITE® LB 8504™

General Purpose



LB 8150™
Silver



Temperature Range:
-29°C to 871°C



Metal Free: No

Colour: Silver
Solid Lubricating Agent: Aluminium / Graphite



LB 8060™
Silver (Stick)



Temperature Range:
-29°C to 871°C



Metal Free: No

Colour: Silver
Solid Lubricating Agent: Aluminium / Graphite / Wax



LB 8151™
Silver (Aerosol)



Temperature Range:
-29°C to 871°C



Metal Free: No

Colour: Silver
Solid Lubricating Agent: Aluminium / Graphite



LB 8008™
Copper C5-A



Temperature Range:
-29°C to 982°C



Metal Free: No

Colour: Copper
Solid Lubricating Agent: Copper / Graphite

High Performance



LB 8009™
Heavy Duty



Temperature Range:
-29°C to 1315°C



Metal Free: Yes

Colour: Black
Solid Lubricating Agent: Calcium Fluoride / Graphite



LB 8070™
Heavy Duty (Stick)



Temperature Range:
-29°C to 1315°C



Metal Free: Yes

Colour: Black
Solid Lubricating Agent: Calcium Fluoride / Graphite / Wax



LB 771™
Nickel



Temperature Range:
-29°C to 1315°C



Metal Free: No

Colour: Silver
Solid Lubricating Agent: Nickel / Graphite

