







## TEROSON® Elastomeric Adhesive & Sealant Properties Chart



TEROSON® PRODUCT	ITEM NUMBER	PACKAGE TYPE/SIZE	COLOR	EXTRUSION RATE <sup>1</sup> (g min.)	CURE METHOD	SKIN TIME (min.)	TEMPERATURE RANGE	SHORE HARDNESS	TENSILE STRENGTH <sup>2</sup> (psi)	ELONGATION AT BREAK (%)	SHEAR STRENGTH ON STEEL (psi)	
<b>ELASTOMERIC ADHESIVES</b>	<b>TEROSON® MS 5570™</b>	1565679 1567505* 1578969*	300 ml cartridge 50 lb. pail 250 kg drum	White	150	Moisture	30	-40°F (-40°C) to 200°F (93°C)	A 55	380	230	400
	<b>TEROSON® MS 9360™</b>	2115386	300 ml cartridge	Black	90	Moisture	12	-40°F (-40°C) to 200°F (93°C)	A 55	475	225	425
	<b>TEROSON® MS 9399™</b>	2081733 2081666	400 ml dual cartridge 400 ml dual cartridge	Black White	N/A	Two-Component Static Mix	25	-40°F (-40°C) to 200°F (93°C)	A 60	435	130	290
	<b>TEROSON® MS 9399™ PART A</b>	2037227	29 kg pail	Black								
	<b>TEROSON® MS 9399™ PART B</b>	1306968	29 kg pail	Black								
	<b>TEROSON® MS 9320™</b>	1899447	300 ml cartridge	Grey	NA	Moisture	10 to 20	-22°F (-30°C) to 194°F (90°C)	30	260 (b)	300	200
	<b>TEROSON® MS 9380™</b>	1898443	290 ml cartridge	White	NA	Moisture	5 to 10	-40°F (-40°C) to 212°F (100°C)	65	580 (b)	120% (b)	360
	<b>TEROSON® MS 930™ NA†</b>	2138431 2138430 2138429 2138423 2138422 2138427 2138428 2138425 2138424	290 ml cartridge 290 ml cartridge 290 ml cartridge 20 kg pail 250 kg drum 250 kg drum 570 ml sausage 570 ml sausage 570 ml sausage	Black White Grey Black Black White Black White Grey	NA	Moisture	25 to 40	-58°F (-50°C) to 176°F (80°C)	30	1	250	120
	<b>TEROSON® MS 939™ NA†</b>	2068378 2069997 2069400 2069991 2069992 2069989 2069988 2069990	290 ml cartridge 290 ml cartridge 290 ml cartridge 22.68 kg pail 250 kg drum 570 ml sausage 570 ml sausage 570 ml sausage	Black White Grey Black Black Black White Grey	90	Moisture	5	-40°F (-40°C) to 200°F (93°C)	A 55	390	500	270

ITEMS IN RED = Source's PICK or NEW

\* Made-to-order item. \*\* Uncarded tubes, sold as full cases of 100 pieces. † Agency approval: UL Classified/Listed for the U.S.

## Elastomeric Equipment

LOCTITE® PRODUCT	ITEM NUMBER	PRESSURE REGULATION	USED TO DISPENSE	PACKAGE TYPE & SIZES	VISCOSITY RANGE	LOW LEVEL SENSING	CONSUMABLES - DISPENSE ACCESSORIES
<b>MANUAL CARTRIDGE DISPENSING</b>							
 <b>MANUAL CARTRIDGE APPLICATOR 300 ML</b>	1093940	N/A	Henkel Construction Adhesives, Caulking products in 10 oz. caulking tubes	300 ml cartridges	Medium to High	N/A	Cartridge Accessories - Page 175
<b>PNEUMATIC CARTRIDGE DISPENSING</b>							
 <b>HD10 300 ML PNEUMATIC CARTRIDGE DISPENSER</b>	1714379	0 to 60 psi	Gel Cyanoacrylates, Anaerobic Gasketing, Light Cure/Acrylics, Silicones	300 ml cartridges 250 ml tubes	Medium to High	No	Cartridge Accessories - Page 175
 <b>HIGH PRESSURE 300 ML BENCHTOP CARTRIDGE DISPENSER</b>	1046901	0 to 725 psi	Silicone, Polyurethane, MS Polymer Adhesives	290 ml cartridges 300 ml cartridges 310 ml cartridges	10,000 to 1,000,000 cP	Yes	Use with High Pressure Dispense Valve (sold separately) - see below
 <b>SOFT PRESS HAND HELD PNEUMATIC APPLICATOR</b>	250052	0 to 125 psi	Adhesive Packaged in Soft Packs	Soft Pack	Low to High	N/A	582416 - Soft Press Pneumatic Applicator Nozzle (1)
 <b>TEROSON® MULTIPRESS TELESCOPIC DISPENSER</b>	142241	0 to 145 psi	Sprayable SMP Adhesives	300 ml Cartridge	Low to High	N/A	547882 - Pneumatic Spray Applicator Nozzle Kit (12)
 <b>TEROSON® POWERLINE II 300 ML DISPENSER</b>	960304	0 to 100 psi	MS Polymer Polyurethane	300/310 ml Cartridge	Medium to Very High	N/A	Cartridge Accessories - Page 175

LOCTITE® PRODUCT	ITEM NUMBER	TYPE	VISCOSITY RANGE	DISPENSE PATTERNS	USED TO DISPENSE	STROKE ADJUSTMENT	SUCK-BACK	CONSUMABLES - DISPENSE ACCESSORIES
<b>HIGH VISCOSITY FLUID &amp; PASTE VALVES</b>								
 <b>VA26 DISPENSE VALVE - 50 BAR</b>	1960414	High Viscosity Fluid and Paste Valves	10,000 to 1,000,000 cP	Drop, Bead	Silicones, MS Polymers, Urethanes	Yes	Yes	Dispense Tips and Accessories - Pages 174-175
 <b>HIGH PRESSURE DISPENSE VALVE - 150 BAR</b>	1153502	High Viscosity Fluid and Paste Valves	500,000 to 2,000,000 cP	Drop, Bead	Silicones, MS Polymers, Urethanes	Yes	No	Dispense Tips and Accessories - Pages 174-175

The Adhesive Sourcebook 2017: Your Source for LOCTITE® products for design, assembly, manufacturing and maintenance