

Find the right product for your application



GENERAL PURPOSE

LOCTITE® AA 330™

LOCTITE® EA 3801™

SPECIALTY

High Performance

LOCTITE® AA H4800™
LOCTITE® AA H8000™
LOCTITE® EA E-20HP™

Flexible Solutions

LOCTITE® EA E-05CL™
LOCTITE® UK U-09FL™

Special Substrates

LOCTITE® AA 3038™
LOCTITE® Epoxy Weld™

Magnet Bonding

LOCTITE® AA 324™

Potting

LOCTITE® EA E-30CL™
LOCTITE® EA E-60NC™

*Refer to Technical Data Sheet (TDS) for more information.



General Purpose

STRUCTURAL ADHESIVES



AA 330™
Small Gap



EA 3801™
Fast Fixture

THIS PRODUCT REQUIRES
AN ACTIVATOR **SF 7387™**



Fixture Speed: 4 minutes



Substrate: Aluminium, Ceramic, Concrete, Glass, Metal, Stainless Steel, Steel, Wood

Gap: 0.5mm

Temperature Resistance: 120°C

Colour: Pale Yellow

Chemistry: Two-step Acrylic



Working Time: 5 minutes



Substrate: Aluminium, Ceramic, Concrete, Glass, Steel, Wood, Copper Alloys and most Plastics

Temperature Resistance: 65°C

Colour: Translucent Yellow

Chemistry: Epoxy

High Performance

STRUCTURAL ADHESIVES



AA H4800™
High Impact, Environment Resistance



AA H8000™
High Impact, High Peel



Working Time: 30 minutes



Substrate: Acrylonitrile ABS, Aluminium, FRP, Gel Coat, PVC, RTM, Stainless Steel, Mild Steel

Temperature Resistance: 110°C

Colour: Light Yellow

Chemistry: Methyl Methacrylate



Working Time: 15 minutes



Substrate: ABS, Aluminium, FRP, Gel Coat, PVC, RTM, Stainless Steel, Mild Steel

Temperature Resistance: 100°C

Colour: Green

Chemistry: Methyl Methacrylate



EA E-20HP™
High Shear, High Peel



Working Time: 20 minutes



Substrate: Aluminium, Ceramic, Concrete, Glass, Metal, Steel, Stainless Steel, Wood

Temperature Resistance: 80°C

Colour: Off-white

Chemistry: Epoxy