

Find the right product for your application



GENERAL PURPOSE

LOCTITE® AA 330™

LOCTITE® EA 3801™

SPECIALTY

High Performance

LOCTITE® AA H4800™
 LOCTITE® AA H8000™
 LOCTITE® EA E-20HP™

Flexible Solutions

LOCTITE® EA E-05CL™
 LOCTITE® UK U-09FL™

Special Substrates

LOCTITE® AA 3038™
 LOCTITE® Epoxy Weld™

Magnet Bonding

LOCTITE® AA 324™

Potting

LOCTITE® EA E-30CL™
 LOCTITE® EA E-60NC™

*Refer to Technical Data Sheet (TDS) for more information.



General Purpose

STRUCTURAL ADHESIVES



AA 330™
 Small Gap



EA 3801™
 Fast Fixture

THIS PRODUCT REQUIRES AN ACTIVATOR **SF 7387™**

Fixture Speed: 4 minutes

Working Time: 5 minutes

Substrate: Aluminium, Ceramic, Concrete, Glass, Metal, Stainless Steel, Steel, Wood

Substrate: Aluminium, Ceramic, Concrete, Glass, Steel, Wood, Copper Alloys and most Plastics

Gap: 0.5mm
Temperature Resistance: 120°C
Colour: Pale Yellow
Chemistry: Two-step Acrylic

Temperature Resistance: 65°C
Colour: Translucent Yellow
Chemistry: Epoxy

High Performance

STRUCTURAL ADHESIVES



AA H4800™
 High Impact, Environment Resistance



AA H8000™
 High Impact, High Peel

Working Time: 30 minutes

Working Time: 15 minutes

Substrate: Acrylonitrile ABS, Aluminium, FRP, Gel Coat, PVC, RTM, Stainless Steel, Mild Steel

Substrate: ABS, Aluminium, FRP, Gel Coat, PVC, RTM, Stainless Steel, Mild Steel

Temperature Resistance: 110°C
Colour: Light Yellow
Chemistry: Methyl Methacrylate

Temperature Resistance: 100°C
Colour: Green
Chemistry: Methyl Methacrylate



EA E-20HP™
 High Shear, High Peel

Working Time: 20 minutes

Substrate: Aluminium, Ceramic, Concrete, Glass, Metal, Steel, Stainless Steel, Wood

Temperature Resistance: 80°C
Colour: Off-white
Chemistry: Epoxy