

THREAD SEALANTS

Product	Item Number	Pack Size	Features	Colour	Viscosity [cP]	Thixotropic [yes/no]	Temperature Range	Breakloose Torque Steel M10, Pre-torqued 5 N.m
METAL								
567™	2087068	6 ml	For Stainless Steel, High temperature, Potable water approval AS/NZS 4020:2018 PTT40069	Off-White	540,000	Yes	-55°C to 250°C	17
	2779093	50 ml						
	2099597	250 ml	AGA Certificate 3207 to 2000 kPa Class III Domestic Gas					
577™	2779092	50 ml	For use with parallel or tapered fittings. Primerless. Medium-High Strength, General Purpose	Yellow	100,000	Yes	-55°C to 180°C	27
	2099610	250 ml	Watermark WMTS 014:2016 certified - WMK26725, AGA Certificate 4787 to 2000 kPa Class III Domestic Gas					
5770™	1138284	50 ml	High temperature for steam application	Grey	Paste	No	-55°C to 280°C	27
561™	943428	19 g	Easy application on hard to reach areas	Off-White	Semi-solid wax	No	-55°C to 150°C	9
542™	470771	10 ml	Hydraulic / pneumatic sealant up to 1", no fillers	Brown	2,000	No	-55°C to 150°C	25
	234422	50 ml						
569™	234473	50 ml	Hydraulic / pneumatic sealant up to 3/4", no fillers	Brown	400	No	-55°C to 150°C	5
	234475	250 ml	AGA Certificate 3375 to 2000 kPa Class III Domestic Gas					
536™	1787978	50 ml	Low breakloose, high lubricating property	Off-White	820,000	No	-55°C to 177°C	0.5
PLASTIC								
SI 5331™	2061031	100 ml	For plastic and metal, silicone based Potable water approval AS/NZS 4020:2018 PTT40032	White	50,000	No	-55°C to 150°C	4.5
55™	473136	160 m	Safe, fast, and easy to use on Metal and plastic threaded fittings, allows reliable post-adjustment, Polyamide based sealing cord Watermark WMTS 014:2016 certified - WMK26725 AGA Certificate 6007 to 2000 kPa Class III Domestic Gas	White	Cord	No	-55°C to 150°C	Not Applicable

