



Hi Temperature Grease IRIX EVO LX 200-2 400g (450g Cartridge)

Description

IRIX EVO LX 200-2 is a calcium sulphonate complex thickened lubricating grease based on mineral oil. These greases contain antioxidants and corrosion inhibitors. They do not contain conventional EP- and AW-additives since they are built in as an integral part of the soap structure.

Advantages

- Very good corrosion protection
- Superb mechanical stability
- Very good water resistance
- Excellent load carrying capacity

TECHNICAL CHARACTERISTICS

Characteristic	Method	IRIX EVO LX 200-2
Thickener		Lithium complex
Texture		Smooth
Colour	Visual	Green
NLGI Grade	ASTM D 217	2
Dropping point	IP 396	> 240 °C
Base oil viscosity at 40 °C	ASTM D 7152	220 mm ² /s
Base oil viscosity at 100 °C	ASTM D 7152	17 mm ² /s
Penetration 60 strokes	ISO 2137	265 - 295
4-ball weld load	ASTM D2596	355 Kg
Water resistance at 90 °C	DIN 51807:1	0-90
Water wash out at 38 °C	ISO 11009	< 5 %
Emcor dist water	ISO 11007	0 - 0
Emcor salt water		≤ 2 - 2
Temperature range		-20 °C to +150 °C (max +160 °C)