



## Nautic Grease - Marine Grade 200g

## Description

High quality Technosynthese® grease formulated with Calcium soap, Extreme Pressure, anti-wear, anti-corrosion and anti-oxidation additives.

Contains PTFE PolytétrafluoroéthylènePolytétrafluoroéthylène) to improve lubricity

## Advantanges

- Insoluble in water
- High level of adherence on surfaces
- High anti-oxidation and anti-corrosion protection in salt water environments
- High anti-wear Extreme Pressure and thermal resistance properties
- High durability for less grease consumption

## TECHNICAL CHARACTERISTICS

Properties		
Colour	Visual	Blue
Consistency grade	DIN 51 818	NLGI 2
Soap	Туре	Calcium
Base oil viscosity at 40 °C	DIN 51 562	195 mm²/s
Base Oil viscosity at 100 ℃	DIN 51 562	15 mm²/s
Drop Point	ASTM D 2265	150 ℃
Penetrability - 60 cycles	ASTM D 217	265 / 295 x 10- <sup>1</sup> mm
Four ball test - welding load	DIN 51 350 T4	4000 N
FAG FE-9 test	DIN 51 821	F50 > 100hr a 120°C (248°F)
SKF EMCOR Test	ASTM D 6138	2/1
Copper corrosion test	ASTM D 4048	1 120
Water Washout	DIN 51 807 T1	0/90