



Product code - 9091

Sterling LITHPLEX EP2 Multi Purpose NLGI 2 Grease - 450g Cartridge & 2.5kg Tub

500g Tub, 20kg Tub, 180kg Tub - Available Upon Request

Features and Benefits

- Excellent extreme pressure performance
- Stays in place to lubricate and seal effectively
- Good mechanical and shear stability
- Excellent rust and corrosion resistance
- Superior oxidation and thermal stability
- Good low temperature performance and pump ability
- Good high temperature performances

Technical Characteristics

Technical Characteristics	
Appearance	Blue, Tacky
NLGI Classification	2
Thickener	Lithium complex
Temperature range	-20°C to 180°C
Dropping Point ASTM D-2265	260°C +
Worked Penetration, 60 Strokes ASTM D-217	265-295
Base Oil Viscosity @ 40 °C ASTM D445	200
Wheel Bearing Leakage, gm. Loss ASTM D-4290	6.0
Rust Prevention, Rating ASTM D-1743	Pass
Copper Corrosion, Rating ASTM D-4048	1b
Oxidation Stability, PSI Drop ASTM D-942	5
Oil Separation, % Loss ASTM-1742	2.5
Four Ball Wear, mm Scar Dia, Max. ASTM D-2266	0.60
Four Ball EP Weld Point, Min. ASTM D-2596	31.5kg
Timken, OK Load, Kg ASTM D-2509	23