



Product code - 9095

Sterling TUFF STUFF High Performance MP EP2 Grease - 450g Cartridge

2.5kg Tub, 20kg Tub, 180kg Tub - Available Upon Request

Features and Benefits

- Protects and lubricates all moving parts particularly under heavy or shock loading conditions
- Excellent mechanical stability that is very important in vibrating environments as inferior mechanical stability can cause the grease softening with loss of lubrication performance and leakage
- Formulated to guarantee a much-improved level of resistance to water wash-out to extend bearing life in wet environments
- Excellent oxidation resistance that provides long service life
- Extra protection against rust and corrosion promotes effective lubrication under difficult environments that may be corrosive or rust prone service situations

Technical Characteristics	
Appearance	Black
NLGI Classification	2
Thickener	Lithium Complex
Temperature range	-20°C to 175°C
Dropping Point ASTM D-2265	260°C +
Worked Penetration, 60 Strokes ASTM D-217	265-295
Base Oil Viscosity @ 40 °C ASTM D445	320
Load Wear Index, Kgs, Min ASTM D-2596	40
Four Ball EP Weld Point, Min. ASTM D-2596	600kg
Timken, OK Load, Kg ASTM D-2509	34
Molybdenum Disulfide, %	5.0 Min