

ULTRA XHP Grease

Heavy Duty Grease - Lithium Complex



Product code - 9113

Sterling ULTRA XHP Heavy Duty Lithium Complex EP2 Grease - 450g Cartridge

400g Aero, 500g Tub, 2.5kg Tub, 20kg Tub, 180kg Tub - Available Upon Request

Features and Benefits

- High viscosity base oil and tackiness resists 'squeeze out' from surfaces under loads
- PTFE is a premium film medium that reduces friction thus increasing lubrication and reducing operating temperatures. Protects against wear on all moving parts from shock loadings to unusually high-load service conditions
- High weld load minimises scuffing and increases wear protection under high load and shock load conditions
- Excellent high shear stability and high temperature operation
- Excellent resistance to water and water wash-out even at elevated temperatures

Technical Characteristics

Technical Characteristics	
Appearance	Purple, Smooth & Tacky
NLGI Classification	2
Thickener	Lithium complex
Temperature range	-20°C to 185°C to 210°C intermittently
Dropping Point ASTM D-2265	250°C min
Worked Penetration, 60 Strokes ASTM D-217	285-305
Water Washout, Wt %, Max ASTM D-1264	3.0
Base Oil Viscosity @ 40 °C ASTM D445	620cSt
Copper Corrosion IP112	Pass
Four Ball Wear, mm Scar Dia, Max. ASTM D-2266	0.48
Four ball EP Weld Load, Min ASTM D- 1763	500kg